

**BONDERITE****BONDERITE S-ST 6776 LO WOD AERO**

Known as TURCO 6776 LO WOD

November 2013

**PRODUCT DESCRIPTION**

BONDERITE S-ST 6776 LO WOD AERO provides the following product characteristics:

<b>Technology</b>	Metal Pre-Treatment
<b>Product Type</b>	Paint Stripper
<b>Application</b>	Spray and manual

BONDERITE S-ST 6776 LO WOD AERO is a low odor, thixotropic paint remover developed for effective stripping of such resistant finishes as epoxies, epoxy primers, polyurethanes, and similar catalyzed paints. BONDERITE S-ST 6776 LO WOD AERO paint remover offers a significant advance in work place safety. It does not contain methylene chloride, chlorinated solvents, phenols, chromates, ammonia or amines. BONDERITE S-ST 6776 LO WOD AERO can be used on aluminum, mild steel, cast iron, and titanium when used as directed. BONDERITE S-ST 6776 LO WOD AERO is not recommended for use on high strength steel or magnesium. BONDERITE S-ST 6776 LO WOD AERO meets the "Effect on Metals" requirements of MIL-R-81903A.

**Application Areas**

BONDERITE S-ST 6776 LO WOD AERO offers these features:

1. Low odor
2. Significantly lower waste disposal costs.
3. Can be easily treated on site (see MSDS)
4. Amount of stripper used less than conventional methylene chloride strippers
5. No flash point to boil (Pensky-Martens)
6. Used as received, No mixing or dilution required
7. Excellent cling to vertical and overhead surfaces
8. Positive pressure air respirators are not required

**TECHNICAL DATA**

Appearance	Viscous white liquid
Viscosity (Brookfield 20° C, 6 rpm), mPa.s	>15,000
pH-value	2.5 to 3.0

**DIRECTION OF USE****Preliminary Statement**

Prior to use it is necessary to read the **Material Safety Data**

**Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed. Please also refer to the local safety instructions and contact Henkel for analytical support.

**Use instructions****Applications:**

Apply a uniform coating to surface being stripped by means of non-atomizing spray. Allow sufficient time for stripper to work. Performance improves as temperature increases. Agitation with a stiff bristle brush will aid in removal of the finish. Repeat if necessary.

**Removal:**

Squeegee off bulk of loosened paint and BONDERITE S-ST 6776 LO WOD AERO, followed by high pressure water rinse.

**Storage**

Temperature, °C	0 to 40
Shelf-life (in unopened original packaging), months	12

**Classification**

Please refer to the corresponding **Material Safety Data**

**Sheets** for details on:

**Hazardous Information**  
**Transport Regulations**  
**Safety Regulations**



## ADDITIONAL INFORMATION

### Disclaimer

#### Note:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

#### **In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:**

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

#### **In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

#### **In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:**

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

#### Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.0